

Data on Proprietary Joints

SUPPLIER	BRAND	MOVEMENT CAPACITY mm						WORKING TEMPERATURE RANGE °C	MAXIMUM SKEW ANGLE DEGREES	DEPTH	INSTALLATION DIMENSIONS mm			DRAINAGE INCORPORATED	HA APPROVED
		HORIZONTAL		VERTICAL	LATERAL	WIDTH	LENGTH								
		COMPRESSION	TENSION												

ASPHALTIC PLUG JOINTS

ASL Contracts	Hotfalt	20	20	5	7	-15 +40	*	min 100	500+	Any	Optional	✓
	Hotfalt Minor	10	10	3	4	-15 +40	*	min 40	200+	Any	Optional	✓
CAMAS Associated Asphalt	Asphapol	20	20	3		-10 +20	90	min 70	500+	Any	Optional	✓
ESS systems	ESS Asphaltic Plug	20	20	±1.5		-30 +45		50/250	300/750	Any	Optional	✓
	ESS Asphaltic Plug 2000	25	25	±1.5		-30 +45		50/250	300/400	Any	Optional	✓
Prismo	Thormajoint	10/25	10/25	±1.5	7	-30 +45	45	50/100	500+	Any	Optional	✓
	Thormajoint 90	35	35	±1.5	7	-30 +40	45	min 100	550+	Any	Optional	✓
	Super-joint	20	20	±1.5	7	-30 +40	45	min 100	300+	Any	Optional	
PSC Freyssinet	VIA joint	10	10	3	5	*	*	60 min	350+	Any	Optional	✓
Universal Sealants	Zebrajoint	20	20	±1.5		-30 +45	*	100	500	Any	Yes	
Zebraflex	Zebrajoint	20/30	20/30	±1.5	7	-30 +45	45	50/250	300/750	Any	Optional	✓

ELASTOMERIC MECHANICAL AND ELASTOMERIC JOINTS

ASL Contracts	Multiflex T30/T330	15/165	15/165	*	*	Any	Any	*	*	*	Optional	✓
Grace/Servicised	Waboflex SR2A/13	25/165	25/165	6	10/125	-40 +60	30	40/127	270/1397	1829/1219	Yes	✓
PSC Freyssinet	M65/200	32/100	32/100	*	*	*	*	*	*	*	Optional	✓
	Eole 700/2500	350/1250	350/1250	*	*	*	*	*	*	*	*	
	N 65	32	32	*	*	*	*	*	*	*	*	✓
Universal Sealants	Transflex 150/1300	19/165	19/165			-15 +35	*	61/153	440/1554	1830/1220	Yes	✓

BURIED JOINTS

ASL Contracts	TU 20/30	10/15	10/15		*	Any	*	30	210	Any	No	
	Avon joint	14	14		*	Any	*	*	*	*	*	✓
ESS systems	Fleximat	±10	±10			Any	*	*	*	Any	No	
Universal Sealants	Uniflex	15	15	*	*	Any	*	*	*	Any	No	

(* - Consult manufacturer)